

ERTOIL MULTICAR 15W40

DESCRIPTION



Mineral multi-grade lubricant oils, suitable for use in petrol and GLP engines and indirect injection diesel engines with a pre-chamber, in cars and light commercial vehicles in severe use.

Applications

- Suitable for petrol, GLP and diesel engines, both aspirated and with turbo-compressors.

Performance

- Good for all seasons of the year, it guarantees good lubrication of the entire engine when starting up, even at low temperatures.
- Because of its special additives, it reduces friction between the metal parts of the engine, preventing possible wear or seizing up.
- High detergent/dispersant level, which prevents the build-up of sludge and dirt in the engine, keeping it clean and protected.

SPECIFICATIONS

· ACEA A3/B3- 12

| · API SL/CF

TYPICAL CHARACTERISTICS

CHARACTERISTICS	UNITS	METHOD	ERTOIL MULTICAR 15W40
SAE Grade	-	-	15W40
Density at 15°C	g/ml	ASTM D 4052	0,8846
Viscosity at 100°C	cSt	ASTM D 445	14,3
Viscosity at 40°C	cSt	ASTM D 445	105
Viscosity index	-	ASTM D 2270	139
CCS viscosity at -20°C	cP	ASTM D 5293	5800
Pour point	°C	ASTM D 97	-30
Flash point V/A	°C	ASTM D 92	>200
Base number, TBN	mg KOH/g	ASTM D 2896	11
Sulphated ash	% (m/m)	ASTM D 874	1,2
HTHS viscosity at 150°C	cP	ASTM D 4683	3,9

HEALTH & SAFETY and ENVIRONMENT

Health, safety and environmental information is provided for this product in the Materials Safety Data Sheet. This gives details of potential hazards, precautions and First Aid measures together with environmental effects and disposal of used products.